

Surface Conditioning Quick Change Discs

Roloc® Style - Type R (3M)

Diameter	Min.	Grade	P/N	Each
1-1/2"	50	Coarse	62-0280	0.560
1-1/2"	50	Medium	62-0284	0.560
1-1/2"	50	Very Fine	62-0288	0.560

Roloc® Style - Type R (3M)

Diameter	Min.	Grade	P/N	Each
2"	50	Coarse	62-0281	0.870
2"	50	Medium	62-0285	0.757
2"	50	Very Fine	62-0289	0.757

Roloc® Style - Type R (3M)

Diameter	Min.	Grade	P/N	Each
3"	25	Coarse	62-0282	1.684
3"	25	Medium	62-0286	1.451
3"	25	Very Fine	62-0290	1.451

Roloc® Style - Type R (3M)

Diameter	Min.	Grade	P/N	Each
4"	10	Coarse	62-0180	2.786
4"	10	Medium	62-0183	2.358
4"	10	Very Fine	62-0198	2.358

Turn On Style - Type S (Standard, Norton)

Diameter	Min.	Grade	P/N	Each
1-1/2"	50	Coarse	63-0318	0.560
1-1/2"	50	Medium	63-0215	0.560
1-1/2"	50	Very Fine	63-0210	0.560

Turn On Style - Type S (Standard, Norton)

Diameter	Min.	Grade	P/N	Each
2"	50	Coarse	63-0205	0.870
2"	50	Medium	63-0208	0.757
2"	50	Very Fine	63-0211	0.757

Turn On Style - Type S (Standard, Norton)

Diameter	Min.	Grade	P/N	Each
3"	25	Coarse	63-0206	1.684
3"	25	Medium	63-0209	1.451
3"	25	Very Fine	63-0212	1.451

Turn On Style - Type S (Standard, Norton)

Diameter	Min.	Grade	P/N	Each
4"	10	Coarse	63-0207	2.786
4"	10	Medium	63-0328	2.358
4"	10	Very Fine	63-0329	2.358